

Requested Patent: WO9429187A1
Title: SELF-CLOSING APPARATUS ;
Abstracted Patent: US5857595 ;
Publication Date: 1999-01-12 ;
Inventor(s): NILSON BILLY (SE) ;
Applicant(s): ;
Application Number: US19960553505 19960321 ;
Priority Number(s): SE19930001924 19930604; WO1994SE00476 19940520 ;
IPC Classification: B65D37/00 ;

Equivalents:

AU6986394, DE69405393D, DE69405393T, EP0700353, FI955296, JP3327472B2,
JP9502409T, NO307776B, NO954477, SE501740, SE9301924 ;

ABSTRACT:


PCT No. PCT/SE94/00476 Sec. 371 Date Mar. 21, 1996 Sec. 102(e) Date Mar. 21, 1996 PCT Filed May 20, 1994 PCT Pub. No. WO94/29187 PCT Pub. Date Dec. 22, 1994 This invention relates to a self-closing apparatus which enables flowable substance present in a container to be dispensed therefrom. The apparatus includes a flexible diaphragm having an outlet aperture, and a stud which is fixed in relation to the diaphragm and which is located inwardly thereof, wherein the stud so coacts with the outlet aperture that the diaphragm in its normal position will rest with its outlet aperture resiliently in abutment with the stud and therewith close the container, and so that upon application of a pressure difference across the diaphragm to dispense substance from the container, the diaphragm will resiliently move away from the stud and therewith expose the outlet aperture. The diaphragm includes at least two deformation zones which are spaced at different distances from the outlet aperture, wherein these deformation zones extend around the outlet aperture, and are disposed as concentric circles having a center in the outlet aperture, and have the form of folds which include weakenings in the diaphragm thickness, thereby enabling the remainder of the diaphragm to have an uneven thickness without detrimentally affecting the mutual coaction between stud and diaphragm as the closure apparatus opens and closes.



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : B65D 47/22, 47/24, 83/00	A1	(11) International Publication Number: WO 94/29187 (43) International Publication Date: 22 December 1994 (22.12.94)
(21) International Application Number: PCT/SE94/00476 (22) International Filing Date: 20 May 1994 (20.05.94) (30) Priority Data: 9301924-8 4 June 1993 (04.06.93) SE (71)(72) Applicant and Inventor: NILSON, Billy [SE/SE]; Halle- vadsgatan 2, S-595 35 Mjölby (SE). (74) Agent: BLOMBERG & CO., SKANDINAVISKA PATENT- BYRÅN AB; P.O. Box 14031, S-104 40 Stockholm (SE).	(81) Designated States: AT, AU, BB, BG, BR, BY, CA, CH, CZ, DE, DK, ES, FI, GB, HU, JP, KP, KR, KZ, LK, LU, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SK, UA, US, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>In English translation (filed in Swedish).</i>	

(54) Title: A SELF-CLOSING ARRANGEMENT



(57) Abstract

This invention relates to a self-closing arrangement which enables flowable substance present in a container to be dispensed therefrom. The arrangement includes a flexible diaphragm having an outlet aperture, and a preferably conical stud which is fixed in relation to the diaphragm and which is located inwardly thereof, wherein the conical stud so coacts with the outlet aperture that the diaphragm in its normal position will rest with its outlet aperture resiliently in abutment with the stud and therewith close the container, and so that upon application of a pressure difference across the diaphragm to dispense substance from the container, the diaphragm will resiliently move away from the stud and therewith expose the outlet aperture. The diaphragm (3) includes at least two deformation zones (5, 6) which are spaced at different distances from the outlet aperture (4), wherein these deformation zones (5, 6) extend around the outlet aperture (4) and have the form of folds which include weakenings (7) in the diaphragm thickness, thereby enabling the remainder of the diaphragm (3) to have an uneven thickness without detrimentally affecting the mutual coaction between stud (8) and diaphragm (3) as the closure arrangement opens and closes.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

A SELF-CLOSING ARRANGEMENT

TECHNICAL FIELD

5 The present invention relates to a self-closing arrangement which will allow a flowable substance, such as flowable foodstuffs of different kinds, to flow from a container in which they are contained, wherein the arrangement includes a flexible diaphragm having an outlet aperture, and a preferably
10 conical stud or pin which is fixedly mounted in relation to the diaphragm and located inwardly thereof, wherein the stud so coacts with the outlet aperture that when the diaphragm occupies a normal position the outlet aperture will rest resiliently against the stud and therewith seal the container,
15 and wherein when a pressure difference is applied across the diaphragm to discharge the content of the container, the diaphragm is distanced from the stud and therewith expose the outfeed aperture.

20 DESCRIPTION OF THE PRIOR ART

Many different solutions concerning self-closing devices for discharging flowable substances from containers of different kinds are known to the art, wherein a typical device will
25 include a resilient diaphragm which seals the outfeed aperture of the device in accordance with the preamble of the following Claim 1.

One such construction is disclosed in U.S. Patent Specification 4,141,474, which teaches a discharge arrangement that can
30 be readily manufactured and used. However, this known arrangement is encumbered with certain drawbacks, primarily with regard to the manufacture of the arrangement. The main difficulty in manufacture resides in injection-moulding the closure diaphragm included in the arrangement, since it has
35 been found difficult to obtain a diaphragm of uniform thickness. Uniform diaphragm thickness is important in order for

the diaphragm to move correctly in relation to the stud coacting therewith, such that the discharge aperture will be opened and closed reliably when the arrangement is active.

- 5 Another construction is disclosed in U.S. Patent Specification 4,699,300.

SUMMARY OF THE INVENTIVE CONCEPT

- 10 An object of the present invention is to avoid the aforesaid drawbacks associated with self-closing closure arrangements for containers and other vessels.

15 In accordance with the inventive concept, this object is achieved by providing the diaphragm with at least two deformation zones which are located at different distances from the diaphragm outfeed aperture, in mutually accordance with the characterizing clause of the following main Claim. These deformation zones enable movement of the diaphragm to be
20 controlled so that its outfeed aperture will always move symmetrically and uniformly in relation to the stud coacting with the diaphragm.

By designing the diaphragm in this way, there is obtained a
25 self-closing closure arrangement which is easy to manufacture in view of the fact that the thickness of the diaphragm is no longer a critical manufacturing parameter, either with regard to its thickness or with regard to a uniform thickness across the diaphragm. An inventive closure arrangement can also be
30 produced cheaply.

Furthermore, there is obtained a self-closing closure arrangement which is both reliable in operation and has a long useful life span.

35

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described in more detail with reference to the accompanying drawings, in which

Fig. 1 is an axial section view of an inventive self-closing
5 closure arrangement mounted on a container, and shows the arrangement from one side with the diaphragm in its rest position, i.e. with the arrangement closed;

Fig. 2 illustrates the closure arrangement of Fig. 1 in an
10 initial opening stage;

Fig. 3 illustrates the closure arrangement of Fig. 1 when fully opened;

15 Fig. 4 is an axial sectional view of an inventive closure arrangement combined with a metering or dispensing device in the form of a dispensing container or dispensing chamber fitted to a container, the the closure arrangement being shown in closed state;

20 Fig. 5 illustrates the assembly of Fig. 4 in a substance metering or dispensing state;

Fig. 6 is an axial section view of an inventive self-closing
25 closure arrangement mounted on a metering or dispensing device with a dispensing limitation in the form of a dispensing chamber in a filling position with the diaphragm in its closing position;

30 Fig. 7 illustrates the assembly of Fig. 6 in a metering or dispensing state;

Fig. 8 is an axial section view of an inventive self-closing
closure arrangement combined with an air-suction dispensing
35 container with the diaphragm in a filling position; and

Fig. 9 illustrates the assembly of Fig. 8 in a metering or

dispensing state.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT OF THE

5 INVENTION

Figs. 1-3 illustrate a preferred embodiment of an inventive closure arrangement which includes a main body 1, seen in section, onto which there is fitted a container 2 which
10 contains a flowable substance. In the illustrated case, the container is compressible, i.e. can be compressed to discharge its contents, and may, for instance, have the form of a conventional tube comprising slightly resilient walls. The main body 1 is preferably made of a plastic material and has
15 the form of an annulus which is pressed or welded over the discharge orifice of the container 2. The main body also includes a diaphragm 3 which is moulded or injection-moulded integrally with the main body 1 and which has a central, circular discharge aperture 4. The diaphragm 3 includes
20 deformation zones in the form of circular folds 5 and 6 located at mutually different distances from the aperture 4 and concentrically therewith. The folds 5, 6 are orientated so that the diaphragm will have a conical shape, with the narrow part of the diaphragm facing in the discharge direction
25 in the proximity of the aperture 4, but has in its entirety, obtained immediately in conjunction with manufacture, a slightly conical shape with the apex of the cone facing inwardly towards the container 2. As illustrated in Fig. 1a, the folds include weakenings 7, preferably in the form of
30 grooves.

The closure arrangement also includes a central stud or pin 8 which has a conical part 9 intended for coaction with the aperture 4 in the diaphragm 3. The stud 8 is held centralized
35 by a slightly conical ring 10, with the aid of spoke-like arms 11.

The annular main body 1 is provided in the proximity of the diaphragm 3 with an internal groove 12 having a shape complementary to the outer contours of the slightly conical ring 10. When mounting the pin 8, the ring 10 is pushed into the groove 12 from that side of the main body, which is intended to face in towards the container 2.

In the constructive design of the closure arrangement, the groove 12 is positioned so that the stud 8 will lie against the aperture 4 and move the diaphragm into abutment with the stud 8 with a predetermined degree of tension. In its normal position, the diaphragm will close the container as illustrated in Fig. 1.

When the internal container pressure is increased, for instance by compressing the container, the diaphragm 3, and therewith the aperture 4, will move away from the conical part 9 of the stud 4, as illustrated in Figs. 2 and 3, and substance contained in the container will be pressed out. As soon as the container pressure is normalized, the tension in the diaphragm will cause the diaphragm to return to the position shown in Fig. 1, therewith reclosing the container.

As the internal container pressure increases, the diaphragm will be deformed primarily uniformly in the folds 5, 6, while remaining parts of the diaphragm will remain essentially unaffected, meaning that the aperture 4 in the diaphragm will be displaced generally rectilinearly and symmetrically in the substance discharge direction to and from the stud 8, and will always return to the same position of origin, which is essential to reliable long-term functioning of the arrangement, and also to avoid the closing movement of the diaphragm being obstructed by dry, caked substance.

Figs. 4-9 illustrate different constructions in which the closure arrangement illustrated in Figs. 1-3 has been combined with different types of metering or dispensing containers.

These combinations enable the inventive closure arrangement to be used together with other standard types of containers, for instance non-compressible containers.

5 In the case of the embodiment illustrated in Figs. 4 and 5, the closure arrangement 1 is mounted at one end of a preferably cylindrical dispensing chamber 13 which has deformable walls and which is provided at its other end with an annular part 14 which includes a check valve. The inner surface of the
10 annular part 14 is provided with internal screw threads 15 for connection to a selected standard container. The annular part 14 includes an inner flange 20 which carries a check valve 16 provided with slide pins 17. Located in the proximity of the slide pins 17 are stop means in the form of hooks 18, and a
15 sealing surface 19 which limits movement of the check valve 16 between the open position shown in Fig. 4 and the closed position shown in Fig. 5. When in use, the assembly is intended to be positioned generally vertical, as illustrated in Figs. 4 and 5.

20

In the starting or normal state of the assembly shown in Fig. 4, the check valve 16 is open and the closure arrangement 1 is closed, wherewith flowable substance is able to flow into the dispensing chamber 13 under the force of gravity, until
25 the dispensing container is full.

When substance is to be dispensed, the user squeezes the walls of the dispensing container, either directly or indirectly, as indicated by the arrows 21 in Fig. 5, so as to increase the
30 pressure in the dispensing container in relation to ambient pressure. The check valve 16 is herewith pressed upwards and closes the inlet from the substance container, so as to enable the pressure in the dispensing container to rise sufficiently for the diaphragm 3 to open and for the content of the
35 dispensing chamber 13 to be pressed out through the discharge aperture 4. When the pressure returns to its normal level after use, the check valve is again opened and the diaphragm

3 is again closed.

Figs. 6 and 7 illustrate a variant of the embodiment illustrated in Figs. 4 and 5, wherein the difference between the two embodiments lies mainly in the fact that the check valve 16' is provided with an elongated, tubular body which overlaps and surrounds the stud 8, and the movement of which is controlled or guided by the slide pins 17' and by the stud 8. When the check valve is in its normal, open position, the lower end of the body rests on the arms 11, meaning, among other things, that the hooks 18 mentioned with reference to the preceding Figures are not necessary, which may be an advantage from the aspect of manufacture. Apart from this difference, the arrangement works analogously with the arrangement illustrated in Figs. 4 and 5.

However, an important function of the body 22 is that of providing a dispensing or metering limitation. As evident from Fig. 7, the body 22 limits the extent to which the dispensing chamber is compressed, therewith also limiting the amount of substance that can be dispensed from the dispensing chamber in a definable fashion.

Figs. 8 and 9 illustrate a further variant, including an air-suction container. In the case of this embodiment, the container 13, which has been constructed essentially in the same way as the aforescribed dispensing chambers, is provided with an inventive closure arrangement 1, 1' at both ends thereof, wherein one arrangement, 1, works in the same manner as in the aforescribed embodiment and need not therefore be described in greater detail, whereas the other arrangement functions as an air-suction check valve. Seen constructively, the sole difference with this variant is that the container walls will preferably be highly deformable elastically, and the stud 8' is attached to a disc 23 provided with air holes 24 instead of arms 11.

Fig. 9 illustrates that the valve 1' is closed in the dispensing state of the assembly when the walls of the container 13' are deformed elastically by the user, and shows that the closure arrangement 1 is opened as a result of the higher internal pressure, wherein substance is dispensed.

Immediately the user removes the force acting on the container 13, the container pressure will fall and therewith cause the closure arrangement 1 to close. Because the container walls are elastic, the walls will strive to retake their original form, therewith causing the pressure in the container to fall further, wherein the valve 1' is opened and air is able to flow into the container and equalize the container pressure so that the valve 1' is again closed.


It will be understood that the described and illustrated embodiments of the invention can be modified in many ways within the scope of the following Claims.



For instance, the pressure difference across the valve can be achieved in ways other than by deforming the walls of the containers or chambers. For instance, this pressure difference may be achieved alternatively with the aid of a displaceable plunger or like device.



CLAIMS



1. A self-closing arrangement which permits a flowable substance present in a container to be dispensed therefrom,
5 wherein the arrangement includes a flexible diaphragm having an outlet aperture, and a preferably conical stud which is fixed in relation to the diaphragm and which is located inwardly thereof, wherein the conical stud so coacts with the outlet aperture that the diaphragm in its normal position will
10 rest with its outlet aperture resiliently in abutment with the stud and therewith close the container, and so that upon application of a pressure difference across the diaphragm to dispense substance from the container, the diaphragm will resiliently move away from the stud and therewith expose the
15 outlet aperture, characterized in that the diaphragm (3) includes at least two deformation zones (5, 6) which are spaced at mutually different distances from the outlet aperture (4), wherein these deformation zones (5, 6) extend around the outlet aperture (4) and have the form of folds
20 which include weakenings (7) in the diaphragm thickness, thereby enabling the remainder of the diaphragm (3) to have an uneven thickness without detrimentally affecting the mutual coaction between stud (8) and diaphragm (3) as the closure arrangement opens and closes.
25
2. An arrangement according to Claim 1, characterized in that the weakenings (7) are in the form of grooves.
3. An arrangement according to Claim 1 and 2, characterized
30 in that the diaphragm (3) is circular; and in that the outlet aperture (4) is in the form of a centrally positioned circular hole (4).
4. An arrangement according to any one of the preceding
35 Claims, characterized in that the deformation zones are disposed as concentric circles having a centre in the outlet aperture (4).

1 / 4









INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 94/00476

A. CLASSIFICATION OF SUBJECT MATTER

IPC5: B65D 47/22, B65D 47/24, B65D 83/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC5: B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US, A, 4141474 (NILSON), 27 February 1979 (27.02.79), figure 1, abstract --	1-4
A	US, A, 4699300 (BLAKE), 13 October 1987 (13.10.87), figure 1, abstract -- -----	1-4

☐ Further documents are listed in the continuation of Box C.
 ☒ See patent family annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

& document member of the same patent family

Date of the actual completion of the international search

14 Sept 1994

Date of mailing of the international search report

21 -09- 1994

 Name and mailing address of the ISA/
 Swedish Patent Office
 Box 5055, S-102 42 STOCKHOLM
 Facsimile No. +46 8 666 02 86

Authorized officer

 Kerstin Hällgren
 Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

Information on patent family members

27/08/94

International application No.

PCT/SE 94/00476

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US-A- 4141474	27/02/79	AU-B- 516494	04/06/81	
		BE-A- 856650	31/10/77	
		CA-A- 1093034	06/01/81	
		DE-A- 2731088	12/01/78	
		FR-A,B- 2357434	03/02/78	
		GB-A- 1583494	28/01/81	
		LU-A- 77721	07/10/77	
		NL-A- 7707643	11/01/78	
<hr/>				
US-A- 4699300	13/10/87	NONE		
<hr/>				